


HTS 200 DALI DIM HIGH-BAY LUMINAIRE CLEAR GLASS 60°



SPECIFICATION TEXT

HTS200, LED high-bay luminaire, round, with NICHIA 30-30 SMD LED technology; suspended mounting incl. 3 m connecting cable and snap hook with steel cable as drop guard. Mounting of the luminaire on chain or rope (not included in delivery) via the centrally positioned eyebolt. Surface mounting on wall or ceiling by use of the mounting bracket (MGL0147 to be ordered separately). Luminaire dimensions: ø 390mm, height: 215mm. Weight: 7.3kg. Housing for the optical system made of die-cast aluminium with integrated cooling ribs, powder-coated in grey (similar to RAL9006). Driver housing (on top of the optical system housing) made of die-cast aluminium in black. Driver: Meanwell, dimmable DALI 50/60 HZ. Aluminium anodized reflector (in optical system housing) with narrow-beam light distribution of 60°. Optical system closed by clear safety glass. Fixed light head. Colour temperature 4000K – colour rendition CRI Ra>80, SDCM<4, luminaire luminous flux 22390 lm at 200W power consumption. System efficiency 112 lm/W. Permitted ambient temperature (ta): from -25°C to +45°C | Degree of protection IP65 | Impact resistance IK08. Electrical protection class I, Product service life: 50,000 h at 25° C | L80- B10. D mark | suitable for fire hazardous locations. ENEC certified. CE test mark.

Accessories: MGL0147 mounting bracket complete for wall or ceiling mounting



PRODUCT FEATURES & TECHNICAL DATA

Application area	production sites, warehouses, sales areas, terminals
Luminaire type	LED High-Bay luminaire, round
Light head	fixed
Light source	NICHIA 30-30 SMD LED
Mounting	suspended surface mounted, see accessories
Luminaire optic	aluminium reflector anodized 60° – clear safety glass as cover
Connected load	200 W
Operating current	1.3 A
Operating voltage	AC 230 V
Colour temperature	4000 K
Rated luminous flux	22390 lm
Light output ratio	1
Luminous efficiency	112 lm/W
Colour rendition index	>80
Colour tolerance	SDCM <4
Luminaire colour	grey – similar to RAL9006 + black (driver)
Electrical design	dimmable DALI
Connection method	connection cable 3m (3x1mm²) for on site connecting socket
Degree of protection	IP65
Protection class	I
Impact resistance	IK 08
Height	215 mm
Outer diameter	390 mm
Weight	7.3 kg

DRIVER INCLUDED 230V 50/60 HZ, DALI DIM

QUANTITY OF HIGH-BAY LUMINAIRES PER TYPE OF MINIATURE CIRCUIT BREAKER

	Qty. of highbay luminaires per type of min. circuit breaker		Inrush current ½ value time at typical mains impedance	
	B16 pcs. max.	C16 pcs. max.		
MGL3518	2	3	75 A	680 µS

LIGHT DISTRIBUTION

Distance	Light cone	Lx E _m
1 m	1.50 m ø	6860 Lx
2 m	2.80 m ø	1680 Lx
3 m	4.20 m ø	725 Lx
4 m	5.50 m ø	410 Lx
5 m	7.00 m ø	260 Lx

4000 K